

TORO

Multi Pro[®] WM

200 Gallon (757 L) Sprayer Accessory Workman HD Series

PRECISE SPRAY CONTROL FOR A WORKMAN[®] VEHICLE.

The all-new Multi Pro WM advanced spray system for Toro's Workman[®] HD or the HDX utility vehicle leverages the advanced spray system capability of Toro's Multi Pro 5800, 300 gallon sprayer (1,136 L), and combines the spray system functionality with cutting-edge and intuitive sprayer controls to create the most advanced, efficient and accurate 200 gallon (757 L) bed-mounted sprayer accessory for a utility vehicle on the market. Aggressive agitation, faster response times, consistent and accurate application rates, intuitive rate set up, this sprayer has it all.



toro.com/multipro

F E A T U R E S

Six Diaphragm Pump

An industry exclusive – this oversized pump satisfies the highest spray rates while simultaneously supplying generous agitation flow.

200 gal (757 L) Elliptical Chemical Tank

Thoughtfully redesigned polyethylene tank has no shelves or corners for chemical to stick on, which helps ensure a 99% spray out of chemical.

Sprayer Control Console

InfoCenter™ pressure gauge and sprayer control switches are all located in a unique console featuring Toro's exclusive 'Quick Find™' feature which intuitively helps the operator find boom and actuator switches on the console without looking at them.

Rugged Triangular Spray Boom

Three section, 18.5' (5.6 m) boom width provides fore and aft breakaway on impact while protecting nozzles. Raises into a crisscross position for storage and transportation.

SPRAYER SPECIFICATIONS

SOLUTION TANK	High-density, impact resistant polyethylene with large 16" (41 cm) fill well, tapered bottom and sump with drain.
RATED CAPACITY	200 gallons (757 liters).
SPRAY PUMP	Hardi 363/10.0, six diaphragm positive displacement with 1" (2.5 cm) input shaft; Input speed 0-540 rpm; Flow rate 49 gpm (185.5 lpm) @ 40psi (540 rpm).
AGITATOR	Four side-mounted jet agitation nozzles for full tank agitation.
CONTROLS	Spray pump control switch, agitator jet switch, rate switch, individual boom on/off switches, boom actuator switches, indicator lights on pump, agitation and boom switches, throttle lock.



OPEN BOOMS (STANDARD)

BOOM ASSEMBLY	18.5' (5.6 m) three section, triangular truss style open booms.
BOOM ACTUATORS	Heavy-duty hydraulic lift actuators with nitro-steel-plated shafts; 1 3/4" (4.4 cm) bore x 10.06" (25.5 cm) stroke.
SPRAY NOZZLES	Eleven nozzles turrets, triple turret mount, quick disconnect with diaphragm check valves.


MULTI PRO WM ACCESSORIES

CLEANLOAD™ EDUCTOR KIT	This onboard mixing station allows rapid and safe loading of any chemical without the need to first mix into a slurry. Incorporates a built-in bottle wash nozzle and has an optional suction lance to pull in powdered or liquid products from their container. Stores within the width of the machine.
FRESH WATER RINSE KIT	Simplifies and automates the triple-rinse process, saving hours and hours of clean up time.
ELECTRIC HOSE REEL KIT	150' (45.7 m) of hose for hand or walk spraying applications. Convenient electric powered rewind. Spray gun has an adjustable nozzle from stream to fan.
PRO FOAM™ MARKING KIT	Foam dollops ensure accurate parallel path tracking. Select foam independently or both simultaneously.
ULTRA SONIC BOOM™ KIT	New sonar sensors automatically maintain proper spray height over undulating turf.
COVERED BOOM KIT	Extends 12" (30.5 cm) below the boom to minimize chemical drift in breezy conditions while retaining full boom system functionality.
AIR INDUCTION TURBO TWIN JET NOZZLES	Exclusive to Toro in the 0.8 gpm (3.02 lpm), 1.0 gpm (3.79 lpm) and 1.5 gpm (5.68 lpm) sizes, for exceptional contact coverage.
CONTACT & SYSTEMIC NOZZLES	See complete nozzle listing in the Multi Pro Nozzle Selection Brochure – available for download on toro.com .

WARNING
 THE WORKMAN™ IS AN OFF-HIGHWAY VEHICLE, AND IS NOT DESIGNED, EQUIPPED, OR MANUFACTURED FOR USE ON PUBLIC STREETS, ROADS OR HIGHWAYS.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual Products offered for sale may vary in use, design, requirements and safety features. Consult your local Toro Distributor. "Cushman" is a registered trademark of Ransomes.

The Workman utility vehicle is manufactured in Tomah, WI ISO 9002 Certified Plant.



toro.com
 Worldwide Headquarters
 The Toro Company
 8111 Lyndale Ave. So.
 Bloomington, MN 55420 U.S.A.
 Phone: (1) 952 888 8801
 Fax: (1) 952 887 8258

Printed in U.S.A.
 ©2016 The Toro Company.
 All Rights Reserved.
 200-7260 GB



  
facebook.com/ToroCompany
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope

TORO
 Count on it.