

WHY SETTLE? LEAVE THE GUESSWORK TO THE OTHER GUYS.

The ProPass 200 series broadcast-style topdressers provide the ultimate in application versatility and precision. Intuitive colour-coded adjustment settings deliver extremely accurate spread patterns from ultra-light dustings to ultra-heavy aeration hole filling applications from the first pass to the last, without the guesswork. The unique four-wheel, walking-beam suspension means a light footprint that is easy on the most sensitive turf. Select from a range of configurations and controls to match your needs, tow vehicle and budget. If you are looking for one topdresser to do it all, the ProPass 200 is the only one.



Trailer version

- Chassis with four-wheel, walking-beam suspension
- 8.2 kW (11 hp) engine-powered hydraulics or vehicle-powered hydraulics



Utility vehicle, mounted version

- Vehicle-powered hydraulics
- Storage stands for removal and storage

toro.com/cultivation

FEATURES

Accurate

The colour-coded operating system delivers a perfect spread every time. Repeatable settings for consistent operation and defined edges.

Wireless remote operation

Available wireless controller allows for real-time adjustments. Make quick setting changes and store settings for future use. Base model features a wired controller.

Spread consistency

Ultra light to ultra heavy – evenly apply materials from 2.74 m (9') narrow to 9.1 m (30') wide with the use of our unique "drop zone" patented sliding adjustment.

Dependable

Low maintenance and easy cleaning procedures provide long life and solid performance.

Versatile

The twin spinner accessory can be swapped out with a 180-degree swivel cross-conveyor quickly and easily, without tools.

Choice of configurations

Available as a bed-mounted version, a trailer version with either engine or vehicle hydraulic power, or as a fifth-wheel trailer version.

The ProPass 200 series broadcast-style topdressers provide the ultimate in application versatility. Intuitive colour-coded adjustment settings deliver extremely accurate spread patterns from ultra-light dustings to ultra-heavy aeration filling applications. The four-wheel, walking-beam suspension means a light footprint that is easy on the most sensitive turf. If you are looking for one topdresser to do it all, the ProPass 200 is the only one. A choice of bed-mounted or trailer configurations and manual or wireless controls.

PROPASS 200, MODEL 44701 / PROPASS 200 WIRELESS, MODEL 44751*																			
GENERAL	Hopper Capacity: 0.54 m ³ / 21 ft ³ struck (0.71 m ³ / 25 ft ³ heaped) Controls: standard or electronic wireless Belt: One-piece vulcanised, self-tracking (no seams or staples) Hydraulic Power Pack (optional): 8.2 kW (11 hp) engine Cross conveyor/swivel kit assembly (option): cross conveyor rotates 270 degrees and extends up to 137 cm (54.5") from centre line of topdresser																		
SPREAD WIDTH	Variable, up to 9.1 m (30')																		
WEIGHT	Truck mount base model: 247.6 kg (546 lb) Tow behind chassis: 217.7 kg (480 lb) Truck mount kit: 40.8 kg (90 lb) Twin spinner: 63.5 kg (140 lb) Truck mount storage stand: 29.4 kg (65 lb) Hydraulic power pack engine: (dry) 99.8 kg (220 lb) Cross conveyor/swivel kit assembly: 65.3 kg (140 lb)																		
DIMENSIONS	<table border="1"> <thead> <tr> <th>Tow-behind configuration</th> <th>Truck mount configuration</th> <th>Cross conveyor configuration</th> </tr> </thead> <tbody> <tr> <td>Length 3.4 m (134")</td> <td>Length 1.98 m (78")</td> <td>Length 1.65 m (65")</td> </tr> <tr> <td>Height 1.42 m (56")</td> <td>Height 1.4 m (56")</td> <td>Belt width: 20.3 cm (8") seamless</td> </tr> <tr> <td>Width 1.65 m (65")</td> <td>Width 1.65 m (65")</td> <td></td> </tr> <tr> <td>Total unit weight: 528.8 kg (1,166 lb)</td> <td>Total unit weight: 351.9 kg (776 lb)</td> <td></td> </tr> <tr> <td>Payload 907 kg (2,000 lb)</td> <td>Payload: 907 kg (2,000 lb)</td> <td></td> </tr> </tbody> </table>	Tow-behind configuration	Truck mount configuration	Cross conveyor configuration	Length 3.4 m (134")	Length 1.98 m (78")	Length 1.65 m (65")	Height 1.42 m (56")	Height 1.4 m (56")	Belt width: 20.3 cm (8") seamless	Width 1.65 m (65")	Width 1.65 m (65")		Total unit weight: 528.8 kg (1,166 lb)	Total unit weight: 351.9 kg (776 lb)		Payload 907 kg (2,000 lb)	Payload: 907 kg (2,000 lb)	
Tow-behind configuration	Truck mount configuration	Cross conveyor configuration																	
Length 3.4 m (134")	Length 1.98 m (78")	Length 1.65 m (65")																	
Height 1.42 m (56")	Height 1.4 m (56")	Belt width: 20.3 cm (8") seamless																	
Width 1.65 m (65")	Width 1.65 m (65")																		
Total unit weight: 528.8 kg (1,166 lb)	Total unit weight: 351.9 kg (776 lb)																		
Payload 907 kg (2,000 lb)	Payload: 907 kg (2,000 lb)																		
TYRES ON CHASSIS	24 x 13-12, 4-ply Suspension: 4-wheel walking beam																		
TOW VEHICLE REQUIREMENTS	Towing capacity: 1542 kg (3,400 lb) Tongue weight: 136 kg (300 lb)																		
HYDRAULICS	Minimum 23 l/m @ 138 bar (2,000 psi) Maximum 38 l/m @ 190 bar (2,800 psi)																		
WARRANTY	Two-year warranty. Refer to operator's manual for further details.																		
CE REQUIREMENTS	Meets the CE requirements for the EU																		

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your Toro Distributor.



toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801

©2023 The Toro Company.
All rights reserved.
23-250-GB



facebook.com
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope



Count on it.