eProStripe® 560/ProStripe® 560 **Striping Mower**

PERFECT PITCH.

The lightweight, superb collection and striping performance capabilities are further enhanced on the lithium-ion batterypowered eProStripe by quiet operation, low vibrations levels, and zero engine exhaust emissions. With two of Toro's 60V* Flex-Force Power System® batteries, the electric version is ensured a long run time as well as compatibility across a wide range of hand tools and machinery.

toro.com

A T U R E

High Definition Stripes

· Precisely formulated roller leaves crisp, visually striking stripe while keeping overall weight of machine low to nurture grass blade health and avoid compaction

One Pass Operation

Mow, remove divots and debris, and smooth Agility & Mobility in one wide pass

Fine Turf Performance

• Low cutting height ability designed for sports fields and high impact settings

Powered Transport

· Use traction drive independent of the cutting blade for easy no-mow travel between sites

Flex-Force Power System


• Electric power version of the eProStripe 560 • Variable speed electric uses two Toro-designed 60V* lithium batteries to ensure long, quiet run time, while maintaining compatibility with over 50 Flex-Force tools

· Two piece, ribbed roller allows zero-turn ability to prevent wheel tear while giving superior traction



MatchDrive®

transmission system provides three preset speeds, consistent with the



Grooming Ease

• Enhance appearance and turf health with optional brush kit that stands up grass blades for a cleaner cut, reduces lateral blade growth and loosens debris for removal



^{*} Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load

ePROSTRIPE® 560 / PROSTRIPE® 560 SPECIFICATIONS*

	ePROSTRIPE 560, MODEL 02660T (TOOL ONLY)*	PROSTRIPE 560, MODEL 02657*
CUTTING WIDTH	22" (56 cm)	
ROLLER WIDTH	20.5" (52 cm)	
REAR ROLLER	Steel, two-piece. Ribbed for superior traction and perfect striping	
POWER	2 kW 60V** brushless DC	Kawasaki® FJ180VKAI OHV 4-cycle, gasoline, 179 cc
AIR FILTER	N/A	Dual Element
FUEL TYPE/CAPACITY	Lithium-ion	Gasoline/0.45 gal (1.7 L)
BATTERY SYSTEM	Flex-Force Power System® All battery types, minimum recommendation 2 x 7.5 Ah batteries.	N/A
STARTER	Push button	Pull start
DRIVE SYSTEM	MatchDrive®, electric, operates independent to cutter blade	3-speed self propelled
MOWING SPEED	3-speed 1.9, 2.5 or 3.2 mph (3.0, 4.0 or 5.2 km/h), or variable speed 1.0–3.5 mph (1.6–5.6 km/h)	3-speed 1.9, 2.5 or 3.2 mph (3.0, 4.0 or 5.2 km/h)
BLADE ENGAGEMENT	Push button, operates independent to transmission	Blade Brake Clutch (BBC)
BLADE SPEED	2,800 rpm (standard), 2,400 rpm (ECO mode)	2,700 rpm
DECK	Die cast corrosion-resistant aluminum	
HEIGHT OF CUT RANGE	0.5"-0.236" (13-60 mm)	
HEIGHT OF CUT INCREMENTS	MatchCut™, 0.5" x 0.127" (13 x 3.25 mm) increments	
GRASS BAG CAPACITY	21 gal (80 L)	
DRY WEIGHT	119 lbs (54 kg) w/ optional Groomer Brush (without batteries)	145 lbs (66 kg)
BLADE	1.25" (3.2 mm) thick swagged steel blade	
FRONT TIRES	9" (225 mm) smooth shoulder tire	
DIMENSIONS (L x W x H)	69.1" (175.5 cm) x 23" (58.6 cm) x 40.9" (103.9 cm)	
WARRANTY	Two-year warranty on mower. 3-year warranty on battery (7.5 Ah or greater) and charger (5.4 A & 6-pod chargers)	Two-year warranty. Refer to operator's manual for further details.



134-9600	High-Lift Blade (eProStripe only)
----------	-----------------------------------

Rev. 2/24





Worldwide Headquarters The Toro Company 8111 Lyndale Ave. So. Bloomington, MN 55420 U.S.A. Phone: (1) 952 888 8801

©2024 The Toro Company. All rights reserved. 24-239-master



2







facebook.com twitter.com/TheToroCompany youtube.com/ToroCompanyEurope



^{*} Specifications and design subject to change without notice.

^{**} Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.