

TORO

REELMASTER® 5410/5510/5610

Fairway mowers

LEADING BY REPUTATION.

Performance, productivity and quality are just words if a piece of equipment has not earned them through actual customer usage. After more than 10 years of satisfying customers, the Reelmaster 5410, 5510 and 5610 have earned a reputation for delivering exceptional performance, maximum productivity and high quality. And we haven't stood still over the years. Toro continues to spend time listening closely to our customers to better understand their evolving requirements. Based on customer input, Toro engineers continually work to refine and improve each fairway mower to meet those needs. Everything from operator comfort and efficiency to tractor performance, cutting unit after-cut-appearance improvements and even ease of maintenance is reviewed in our relentless effort to maximise productivity and efficiency.



toro.com/reelmaster

SMART POWER

EdgeSeries™ Reels

F E A T U R E S

Powerful Tier 4 compliant engines

- Featuring Yanmar® 3-cylinder, liquid-cooled, diesel engines.

Smart Power™

- Automatically adjusts the mower's ground speed for the terrain and cutting conditions to maintain the desired reel speed, taking the guesswork out of a consistent cut.

Proven reliability and performance

- Time-tested platform delivers exceptional durability, high performance and versatility.

Unparalleled operator comfort

- With a tilt steering wheel, easy-access steps, a deluxe suspension seat and a well thought-out design that moved the radiator to the rear of the engine compartment to move heat rejection and noise away from operator, these fairway mowers are designed for comfortable, all-day operation.

Outstanding quality of cut

- Dual Precision Adjustment (DPA) cutting units, featuring Toro's EdgeSeries™ reels, combine to deliver a consistent, high-quality cut and superior after-cut appearance, while reducing maintenance with improved reel edge retention.

Enhanced climbing and hillside stability

- CrossTrax® all-wheel drive system is based on the Toro patented Series/Parallel™ design. If one of the front tyres begins to slip, power is transferred to the opposite rear tyre for optimum traction.

Precise monitoring and control

- An onboard InfoCenter allows viewing and changing of settings. It also provides essential information about service intervals, diagnostics and faults.

Electronic cruise control

- Easily keep a consistent speed and reduce fatigue while mowing large areas.

REELMASTER 5410-D TIER 4 DIESEL, MODEL 03952	
ENGINE	Yanmar® 3-cylinder, liquid cooled, diesel engine. 27.5 kW (36.8 hp), 105 N-m (74.4 ft. lb) torque, 1.64 l displacement.
LUBRICATION	Pressurised lubrication system with 4.7 l capacity.
FUEL FILTER	Replaceable spin-on fuel filter/water separator.
AIR CLEANER	Heavy-duty, three-stage, radial seal air cleaner with restriction indicator.
COOLING	Plate and bar radiator/oil cooler combination, 6.3 fins per 2.5 cm (1"), 9.5 l capacity.
FUEL TANK CAPACITY	53 l capacity.
HYDRAULIC OIL CAPACITY	56.8 l capacity.
TRACTION DRIVE	Front-drive wheels powered in a parallel circuit by an electronically controlled hydrostatic pump, with individual wheel motors. All-wheel drive optional with CrossTrax® all-wheel drive system, which transfers power from the front wheels to the opposite rear wheels via independent rear wheel motors.
GROUND SPEED	0–10 mph forward transport; 0–8 mph mow; 0–5 mph reverse transport; 0–4 mph reverse mow.
TYRES	Front traction tyres: 26.5 x 14-12 turf tyres Rear steer tyres: 20 x 12-10
MAIN FRAME	High-strength steel frame with welded construction.
BRAKES	Dynamic braking through hydrostatic traction drive. Parking brake is activated when engine is turned off, when operator leaves seat or by rocker switch.
STEERING	Rear wheel, power steering with an independent hydraulic pump and circuit.
GAUGES	InfoCenter™ onboard LCD display shows gauges, alerts/faults, service reminders and electrical system diagnostics that indicate fuel level, coolant temp., low oil pressure, alternator, engine hours, engine rpm, voltage, reel speed, backlap speed, glow indicator (diesel) and lift/lower indicator.
CONTROLS	Single foot-operated traction pedal. Hand-operated key ignition switch, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch and headlight switch all positioned on right-hand pivoting control console.
ELECTRICAL AND INTERLOCKS	Heavy-duty, 12-volt battery, 570 CCA, 55 amp alternator. Electronic control unit is a microprocessor-based, solid-state control unit with diagnostic capabilities. Traction pedal, parking brake, operator presence in seat and cutting unit engage/disengage safety interlock switches.
REEL DRIVE	Reel drive circuit is split independently for front and rear cutting units. Hydraulic functions controlled by an integrated hydraulic control block. Reel speeds are electronically adjustable in nine incremental settings. Desired clip rate remains consistent as max. mow speed is adjusted. Standard on-board backlapping.
CUTTING UNIT LIFT/LOWER	Front and rear cutting unit lift/lower is sequenced for uniform starting and ending points.
SEAT	Deluxe high-back suspension seat with fore, aft, height and weight adjustment.
ROPS	Standard with seat belt.
HEIGHT	160 cm (63") seat top, 217.2 cm (85") top of ROPS.
LENGTH (2WD)	281.9 cm (111")
WHEEL BASE	152.4 cm (60")
OPERATIONAL WIDTH	288.3 cm (113.5")
TRANSPORT WIDTH	233.7 cm (92")
WEIGHT	1,335 kg (2,943 lb) (2WD), 1,385 kg (3,053 lb) (4WD)
CERTIFICATION	Complies with ANSI B71.4 and CE requirements. Certain machine configurations require rear weight kits for standards compliance; see Operator's Manual for details.
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



8- AND 11-BLADE CUTTING UNITS, MODELS 03621, 03623 AND 03624	
TYPE	5-plex, hydraulically driven, balanced cutting units with adjustable rear weight transfer spring. Cutting units feature quick disconnect for removal/installation and are interchangeable to all positions. Cutting units also feature rear throw capability.
SIZE	56 cm (22") wide, 12.7 cm (5") diameter, 8- and 11-blade cutting units.
WIDTH OF CUT	254 cm (100")
HOC RANGE	8-Blade: 13–38 mm (0.5–1.5"), 11-Blade: 6–19 mm (0.25–0.75")
REEL SPEED	Manually controlled, variable reel speed for control of clip frequency. Reel speeds are incrementally adjustable between 200–2,000 rpm with a backlap speed of 200 rpm.
BEDKNIFE ADJUSTMENT	Dual Precision Adjustment (DPA), bedknife to reel.
ROLLERS	7.6 cm diameter, deep groove plastic Wiehle front roller. 6.4 cm diameter shortened steel rear roller. Other roller configurations optional.

UNIVERSAL GROOMER, MODEL 03763	
TYPE	Forward, reverse and neutral. Rotating blades with optional Broomer™ brush strips that are woven within the blade helix for full width turf contact.
GROOMING WIDTH	52.1 cm (20.5")
GROOMING RANGE	0–6.4 mm (0–0.25") below height of cut when engaged, 0–12.7 mm (0–0.5") above groomer height of cut when disengaged.
BLADES	6.4 cm (2.5") diameter, 1 mm-thick, 36.8 hp heat-treated spring steel blades with 12.7 mm (0.5") spacing.

POWERED REAR ROLLER BRUSH, MODEL 03406	
TYPE	Rotating, helically woven, stiff bristled brush. Spring-loaded belt drive.
CONTACT POINTS	Tightly woven 11-point contact.
SPIN RATE	Rapid 2,000 rpm spin rate.

CUTTING UNITS	
03621	12.7 cm (5") 8-blade DPA RR cutting unit
03623	12.7 cm (5") 11-blade DPA FSR cutting unit
03624	12.7 cm (5") 11-blade DPA RR cutting unit
03618	12.7 cm (5") verticutter cutting unit

TRACTION UNIT ACCESSORIES	
03655	CrossTrax® all-wheel drive kit
03667	Air-ride seat suspension
03614	Golf ball guard

TRACTION UNIT SUNSHADE	
30669	Universal sunshade – White
30671	Universal sunshade – Red
03248	Switch panel
03247	Operator cooling fan
140-1554	Worklights
138-2699	Beacon
138-2994	Wire harness

12.7 cm (5") CUTTING UNIT ACCESSORIES	
03763	Universal groomer
03772	56 cm (22") groomer cartridge
03767	Grooming brush cartridge
03417	Universal only weight kit
03658	Powered rear roller brush for groomers
03413	Weight for cutting units with attachments
03406	Powered rear roller brush only
03411	End weight kit
03415	Flex grass basket
131-6845	Flex groomer rod kit

BEDKNIFE OPTIONS	
137-6094	EdgeMax™
108-9096	Standard
137-6093	EdgeMax low cut
110-4084	Low cut
119-4280	EdgeMax extended low cut
120-1640	Extended low cut
110-4074	Heavy Duty

SCRAPER OPTIONS	
107-3280	Rear roller scraper
107-2993-03	Wiehle roller scraper
110-1735	Comb scraper kit

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



REELMASTER 5510 / 5510-D SPECIFICATIONS*

	REELMASTER 5510, MODEL 03964	REELMASTER 5510-D, TIER 4 DIESEL, MODEL 03954
ENGINE	Kubota® 4-cylinder, liquid cooled, diesel engine. 26.5 kW (35.5 hp) @ 3,000 rpm.	Yanmar® 3-cylinder, liquid cooled, diesel engine. 27.5 kW (36.8 hp), 105 N-m (74.4 ft. lb) torque, 1.64 l displacement.
LUBRICATION	Pressurised lubrication system with 4.7 l capacity.	
FUEL FILTER	Replaceable spin-on fuel filter/water separator.	
AIR CLEANER	Heavy-duty, three-stage, radial seal air cleaner with restriction indicator.	
COOLING	Rear-mounted radiator with industrial tube and fin construction, 6.5 fins per 2.5 cm (1"), 6.6 l capacity.	Plate and bar radiator/oil cooler combination, 6.3 fins per 2.5 cm (1"), 9.5 l capacity.
FUEL TANK CAPACITY	51.1 l capacity. Biodiesel-ready for use up to B20 (20% biodiesel, 80% petroleum blend).	53 l capacity.
HYDRAULIC OIL CAPACITY	34.1 l capacity.	56.8 l capacity.
TRACTION DRIVE	Front-drive wheels powered in a parallel circuit by an electronically controlled hydrostatic pump, with individual wheel motors. All-wheel drive optional with CrossTrax® all-wheel drive system, which transfers power from the front wheels to the opposite rear wheels via independent rear wheel motors.	
GROUND SPEED	0–10 mph forward transport; 0–8 mph mow; 0–5 mph reverse transport; 0–4 mph reverse mow.	
TYRES	Front traction tyres: 26.5 x 14-12 turf tyres Rear steer tyres: 20 x 12-10	
MAIN FRAME	High-strength steel frame with welded construction.	
BRAKES	Dynamic braking through hydrostatic traction drive. Parking brake is activated when engine is turned off, when operator leaves seat or by rocker switch.	
STEERING	Rear wheel, power steering with an independent hydraulic pump and circuit.	
GAUGES	InfoCenter™ onboard LCD display shows gauges, alerts/faults, service reminders and electrical system diagnostics that indicate fuel level, coolant temp., low oil pressure, alternator, engine hours, engine rpm, voltage, reel speed, backlap speed, glow indicator (diesel) and lift/lower indicator.	
CONTROLS	Single foot-operated traction pedal. Hand-operated key ignition switch, mechanical throttle, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch and LED headlight switch all positioned on right-hand pivoting control console.	Single foot-operated traction pedal. Hand-operated key ignition switch, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch and LED headlight switch all positioned on right-hand pivoting control console.
ELECTRICAL AND INTERLOCKS	Heavy-duty, 12-volt battery, 570 CCA, 40 amp alternator. Electronic control unit is a microprocessor-based, solid-state control unit with diagnostic capabilities. Traction pedal, parking brake, operator presence in seat and cutting unit engage/disengage safety interlock switches.	Heavy-duty, 12-volt battery, 570 CCA, 55 amp alternator. Electronic control unit is a microprocessor-based, solid-state control unit with diagnostic capabilities. Traction pedal, parking brake, operator presence in seat and cutting unit engage/disengage safety interlock switches.
REEL DRIVE	Reel drive circuit is split independently for front and rear cutting units. Hydraulic functions controlled by an integrated hydraulic control block. Reel speeds are electronically adjustable in nine incremental settings. Desired clip rate remains consistent as max. mow speed is adjusted. Standard on-board backlapping.	
CUTTING UNIT LIFT/LOWER	Front and rear cutting unit lift/lower is sequenced for uniform starting and ending points.	
SEAT	Deluxe high-back suspension seat with fore, aft, height and weight adjustment.	
ROPS	Standard with seat belt.	
HEIGHT	160 cm (63") seat top, 217.2 cm (85.5") top of ROPS.	
LENGTH (2WD)	281.9 cm (111")	
WHEEL BASE	152.4 cm (60")	
OPERATIONAL WIDTH	288.3 cm (116")	
TRANSPORT WIDTH	233.7 cm (92")	
WEIGHT	1,399 kg (3,083 lb) (2WD), 1,449 kg (3,193 lb) (4WD)	1,420 kg (3,131 lb) (2WD), 1,470 kg (3,241 lb) (4WD)
CERTIFICATION	Complies with ANSI B71.4 and CE requirements. Certain machine configurations require rear weight kits for standards compliance; see Operator's Manual for details.	
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.	

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



8- AND 11-BLADE CUTTING UNITS, MODELS 03638, 03639, 03641 AND 03643	
TYPE	5-plex, hydraulically driven, balanced cutting units with adjustable rear weight transfer spring. Cutting units feature quick disconnect for removal/installation and are interchangeable to all positions. Cutting units also feature rear throw capability.
SIZE	56 cm (22") wide, 17.8 cm (7") diameter, 8- and 11-blade cutting units.
WIDTH OF CUT	254 cm (100")
HOC RANGE	8-Blade: 13-51 mm (0.5-2.0"), 11-Blade: 6-19 mm (0.25-0.75")
REEL SPEED	Manually controlled, variable reel speed for control of clip frequency. Reel speeds are incrementally adjustable between 200-1,650 rpm with a backlap speed of 200 rpm.
BEDKNIFE ADJUSTMENT	Dual Precision Adjustment (DPA), bedknife to reel.
ROLLERS	7.6 cm (3") diameter, deep groove plastic Wiehle front roller. 7.6 cm (3") diameter steel rear roller. Other roller configurations optional.

UNIVERSAL GROOMER, MODEL 03763	
TYPE	Forward, reverse and neutral. Rotating blades with optional Broomer™ brush strips that are woven within the blade helix for full width turf contact.
GROOMING WIDTH	52.1 cm (20.5")
GROOMING RANGE	0-6.4 mm (0-0.25") below height of cut when engaged, 0-6.4 mm (0-0.25") above height of cut when disengaged.
BLADES	6.4 cm (2.5") diameter, 1 mm-thick, heat-treated spring steel blades with 12.7 mm (5") spacing.

POWERED REAR ROLLER BRUSH, MODEL 03408	
TYPE	Rotating, helically woven, stiff bristled brush. Spring-loaded belt drive.
CONTACT POINTS	Tightly woven 11-point contact.
SPIN RATE	Rapid 2,000 rpm spin rate.

CUTTING UNITS	
03638	17.8 cm (7") 8-blade DPA, RR cutting unit
03639	17.8 cm (7") 8-blade DPA, FSR cutting unit
03641	17.8 cm (7") 11-blade DPA, FSR cutting unit
03643	17.8 cm (7") 11-blade DPA, RR cutting unit
03619	17.8 cm (7") verticutter cutting unit

17.8 cm CUTTING UNIT ACCESSORIES	
03768	Universal groomer
03772	56 cm (22") groomer cartridge
03767	Grooming brush cartridge
03418	Universal only weight kit
03659	Powered rear roller brush for groomers
03419	Universal w/RRB weight kit
03408	Powered rear roller brush only
03405	Weight for cutting units without attachments
03415	Flex grass basket
131-6845	Flex groomer rod kit

BEDKNIFE OPTIONS	
137-6094	EdgeMax™
108-9096	Standard
137-6093	EdgeMax low cut
110-4084	Low cut
119-4280	EdgeMax extended low cut
120-1640	Extended low cut
110-4074	Heavy Duty

TRACTION UNIT ACCESSORIES	
03655	CrossTrax® all-wheel drive kit
03667	Air-ride seat suspension
03614	Golf ball guard

SCRAPER OPTIONS	
107-3280	Rear roller scraper
107-2993-03	Wiehle roller scraper
110-1735	Comb scraper kit

TRACTION UNIT SUNSHADE	
30669	Universal sunshade - White
30671	Universal sunshade - Red
03248	Switch panel
03247	Operator cooling fan
140-1554	Worklights
138-2699	Beacon
138-2994	Wire harness

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



REELMASTER 5610 SPECIFICATIONS*

	REELMASTER 5610 4WD, MODEL 03966	REELMASTER 5610-D 4WD, MODEL 03956
ENGINE	Kubota™ 4-cylinder, liquid cooled, diesel engine. 33 kW (44.2 hp) @ 3,000 rpm.	Yanmar® 3-cylinder, liquid-cooled, turbo-diesel engine. 32.4 kW (43.5 hp), 105 N-m (74.4 ft. lb) torque, 1.64 l displacement. Tier 4 final compliant.
LUBRICATION	Pressurised lubrication system with 4.7 l capacity.	
FUEL FILTER	Replaceable spin-on fuel filter/water separator.	
AIR CLEANER	Heavy-duty, three-stage, radial seal air cleaner with restriction indicator.	
COOLING	Rear-mounted radiator with industrial tube and fin construction, 6.3 fins per 2.5 cm (1"), 9.5 l capacity.	
FUEL TANK CAPACITY	51.1 l capacity. Biodiesel-ready for use up to B20 (20% biodiesel, 80% petroleum blend).	
HYDRAULIC OIL CAPACITY	34.1 l capacity.	
TRACTION DRIVE	Electronically controlled hydrostatic pump with individual wheel motors. CrossTrax® all-wheel drive system standard, which transfers power from the front wheels to the opposite rear wheels via independent rear wheel motors.	
GROUND SPEED	0–10 mph forward transport; 0–8 mph mow; 0–5 mph reverse transport; 0–4 mph reverse mow.	
TYRES	Front traction tyres: 26.5 x 14-12 turf tyres; Rear steer tyres: 20 x 12-10.	
MAIN FRAME	High-strength steel frame with welded construction.	
BRAKES	Dynamic braking through hydrostatic traction drive. Parking brake is activated when engine is turned off, when operator leaves seat or by rocker switch.	
STEERING	Rear wheel, power steering with an independent hydraulic pump and circuit.	
GAUGES	InfoCenter™ onboard LCD display shows gauges, alerts/faults, service reminders and electrical system diagnostics that indicate fuel level, coolant temp., low oil pressure, alternator, engine hours, engine rpm, voltage, reel speed, backlap speed, glow indicator (diesel) and lift/lower indicator.	
CONTROLS	Single foot-operated traction pedal. Hand-operated key ignition switch, mechanical throttle, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch and LED headlight switch all positioned on right-hand pivoting control console.	Single foot-operated traction pedal. Hand-operated key ignition switch, cutting unit raise/lower joystick, cutting unit engage switch, parking brake switch, cruise control switch and LED headlight switch all positioned on right-hand pivoting control console.
ELECTRICAL AND INTERLOCKS	Heavy-duty, 12-volt battery, 570 CCA, 40 amp alternator. Electronic control unit is a microprocessor-based, solid-state control unit with diagnostic capabilities. Traction pedal, parking brake, operator presence in seat and cutting unit engage/disengage safety interlock switches.	
REEL DRIVE	Reel drive circuit is split independently for front and rear cutting units. Hydraulic functions controlled by an integrated hydraulic control block. Reel speeds are electronically adjustable in nine incremental settings. Desired clip rate remains consistent as max. mow speed is adjusted. Standard on-board backlapping.	
CUTTING UNIT LIFT/LOWER	Front and rear cutting unit lift/lower is sequenced for uniform starting and ending points.	
SEAT	Deluxe high-back suspension seat with fore, aft, height and weight adjustment.	
ROPS	Standard with seat belt.	
HEIGHT	160 cm (63") seat top, 217.2 cm (85.5") top of ROPS.	
LENGTH	281.9 cm (111")	
WHEEL BASE	152 cm (60")	
OPERATIONAL WIDTH	288.3 cm (114")	
TRANSPORT WIDTH	233.7 cm (92")	
WEIGHT	1,458 kg (3,213 lb)	1,480 kg (3,261 lb)
CERTIFICATION	Complies with ANSI B71.4 and CE requirements. Certain machine configurations require rear weight kits for standards compliance; see Operator's Manual for details.	
WARRANTY	Two-year limited warranty. Refer to the Operator's Manual for further details.	

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



8- AND 11-BLADE CUTTING UNITS, MODELS 03638, 03639, 03641 AND 03643	
TYPE	5-plex, hydraulically driven, balanced cutting units with adjustable rear weight transfer spring. Cutting units feature quick disconnect for removal/installation and are interchangeable to all positions. Cutting units also feature rear throw capability.
SIZE	56 cm (22") wide, 17.8 cm (7") diameter, 8- and 11-blade cutting units.
WIDTH OF CUT	254 cm (100")
HOC RANGE	8-Blade: 13-51 mm (0.5-2.0"), 11-Blade: 6-19 mm (0.25-0.75")
REEL SPEED	Manually controlled, variable reel speed for control of clip frequency. Reel speeds are incrementally adjustable between 200-1,650 rpm with a backlap speed of 200 rpm.
BEDKNIFE ADJUSTMENT	Dual Precision Adjustment (DPA), bedknife to reel.
ROLLERS	7.6 cm (3") diameter, deep groove plastic Wiehle front roller. 7.6 cm (3") diameter steel rear roller. Other roller configurations optional.

UNIVERSAL GROOMER, MODEL 03763	
TYPE	Forward, reverse and neutral. Rotating blades with optional Broomer™ brush strips that are woven within the blade helix for full width turf contact.
GROOMING WIDTH	52.1 cm (20.5")
GROOMING RANGE	0-6.4 mm (0-0.25") below height of cut when engaged, 0-6.4 mm (0-0.25") above height of cut when disengaged.
BLADES	6.4 cm (2.5") diameter, 1 mm-thick, heat-treated spring steel blades with 12.7 mm (5") spacing.

POWERED REAR ROLLER BRUSH, MODEL 03408	
TYPE	Rotating, helically woven, stiff bristled brush. Spring-loaded belt drive.
CONTACT POINTS	Tightly woven 11-point contact.
SPIN RATE	Rapid 2,000 rpm spin rate.

CUTTING UNITS	
03638	17.8 cm (7") 8-blade DPA, RR cutting unit
03639	17.8 cm (7") 8-blade DPA, FSR cutting unit
03641	17.8 cm (7") 11-blade DPA, FSR cutting unit
03643	17.8 cm (7") 11-blade DPA, RR cutting unit
03619	17.8 cm (7") verticutter cutting unit

17.8 cm (7") CUTTING UNIT ACCESSORIES	
03768	Universal groomer
03772	56 cm (22") groomer cartridge
03767	Grooming brush cartridge
03418	Universal only weight kit
03659	Powered rear roller brush for groomers
03419	Universal w/RRB weight kit
03408	Powered rear roller brush only
03405	Weight for cutting units without attachments
03415	Flex grass basket
131-6845	Flex groomer rod kit

BEDKNIFE OPTIONS	
137-6094	EdgeMax™
108-9096	Standard
137-6093	EdgeMax low cut
110-4084	Low cut
119-4280	EdgeMax extended low cut
120-1640	Extended low cut
110-4074	Heavy Duty

TRACTION UNIT ACCESSORIES	
03667	Air-ride seat suspension
03614	Golf ball guard

TRACTION UNIT SUNSHADE	
30669	Universal sunshade - White
30671	Universal sunshade - Red
03248	Switch panel
03247	Operator cooling fan
140-1554	Worklights
138-2699	Beacon
138-2994	Wire harness

SCRAPER OPTIONS	
107-3280	Rear roller scraper
107-2993-03	Wiehle roller scraper
110-1735	Comb scraper kit

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.



toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 USA
Phone: +(1) 952 888 8801

©2023 The Toro Company.
All Rights Reserved.
23-236-GB



facebook.com
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope



Count on it.