

TORO[®]

MH-400

Material handler

THE ORIGINAL MATERIAL HANDLER. AND THEN SOME.

The large-capacity MH-400 delivers versatility and performance to tackle a wide range of jobs at any facility. The cross conveyor is ideal for completing bunker and greens renovations, cart path rebuilding, applying mulch, backfilling of drainage ditches and much more. Install the twin spinner accessory and the MH-400 becomes a large area topdresser to transport and accurately spread materials ranging from crumb rubber to fertiliser, to a sand/peat topdressing mix. The rear hitch receiver allows implements, such as a wood chipper, to be towed in tandem. An integral component of any maintenance programme, the efficient MH-400 reduces labour, saves time and cuts operating costs.

Chassis features a four-wheel, walking-beam suspension for a light footprint on sensitive turf



[toro.com](https://www.toro.com)

F E A T U R E S

Accurate

- Intuitive settings and operating system deliver a perfect spread every time. Repeatable settings for consistent performance and defined edges.

Wireless remote operation

- Available wireless controller allows real-time adjustments. Make quick setting changes and store settings for future use. Base model features a wired controller.

Spread consistency

- Ultra light to ultra heavy – evenly apply materials from 2.74 m (9') narrow to 12.2 m (40') wide with the use of our unique "drop zone" patented sliding adjustment.

Dependable

- All-steel construction, heavy-duty components and low maintenance provide long life and reliable performance.

Versatile

- The twin spinner accessory can be swapped out with a 270°-swivel cross-conveyor quickly and easily without tools. Elevate the rear to a height of 2 m (6') and fill the ProPass topdresser with material, or use as a multi-purpose dump trailer. Standard 2-wheel brakes, optional 4-wheel brakes available.



Twin spinner option

The MH-400 handles everything: topdressing, cross-conveyor, material delivery and hauling/transport. Designed to perform every day as part of your maintenance programme. By being an integral component to daily tasks, the MH-400 reduces labour, saves time and cuts operating costs. Optional wireless remote control available.



MH-400, MODEL 44931 / MH-400 WIRELESS, MODEL 44954*	
GENERAL	Hopper capacity: 3.06 m ³ (4 yd ³) Main conveyor belt: one-piece vulcanised, self-tracking, 76.2 cm (30") wide Controls: standard hydraulic (SH) or electronic hydraulic (EH) Optional accessories: twin spinner assembly, cross-conveyor swivel kit that extends up to 159.5 cm (63.3") from centre line of topdresser
SPREAD WIDTH	Variable, up to 12.2 m (40') using twin spinner accessory
WEIGHT	Base model: 1,360.7 kg (3,000 lb): empty with no options installed
CHASSIS	Payload (tare): 5,352.3 kg (11,800 lb) GVWR: 6,713 kg (14,800 lb) Suspension: 4-wheel walking beam with 10-ply turf tyres Tyre size: 32 x 16.00-15, 10-ply Brakes (electric): 2-wheel standard, 4-wheel optional
DIMENSIONS	Length: 4.8 m (190") Height: 2.2 m (86") Width: 1.98 m (78")
TOW VEHICLE REQUIREMENTS	Towing capacity: 7,189 kg (15,850 lb): maximum payload Minimum power: 33.5 kW (45 hp)
HYDRAULICS	Recommended flow (min no options installed): 23 l/min Recommended flow (min options installed): 38 l/min Recommended input pressure (min): 138 bar (2,000 psi)
WARRANTY	Two-year warranty. Refer to operator's manual for further details.
CE REQUIREMENTS	Meets the CE requirements for the EU

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro distributor.



toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 U.S.A.
Phone: (1) 952 888 8801

©2023 The Toro Company.
All rights reserved.
23-249-GB



facebook.com
twitter.com/TheToroCompany
youtube.com/ToroCompanyEurope



Count on it.